

Section 5: Maintaining Readiness

Topic 25

Hazardous Materials Awareness

Objectives

Welcome to Topic 25.

This topic introduces you to the reporting of hazardous materials (HazMat) incidents and stresses personal safety awareness for emergency communications volunteers.

Student Preparation required:

None.

Introduction

Amateur Radio operators may encounter HazMat incidents during operations, or they may be asked to assist with emergency communications in such incidents. Proper training is required for your own safety. Moreover, a wrong move during a HazMat operation can endanger not only your own safety, but also the safety of other responders, as well as the entire local community.

The term “hazardous materials” (HazMat) refers to any substances or materials, which, if released in an uncontrolled manner (e.g., spilled), can be harmful to people, animals, crops, water systems, and/or other elements of the environment. The list is long and includes explosives, gases, flammable and combustible liquids, flammable solids or substances, poisonous and infectious substances, radioactive materials, and corrosives. Refer to Occupational Safety and Health Administration (OSHA) 29 CFR 1910.1200 and General Services Administration for definitions of hazardous materials. One of the major problems faced by emergency responders is determining which chemicals are involved and their potential hazards.

Hazardous Chemicals on the Move

As the primary regulatory agency concerned with the safe transportation of such materials in interstate commerce, the US Department of Transportation (DOT) has established several

systems to manage HazMat materials. These include definitions of various classes of hazardous materials, placards and other marking requirements for vehicles, containers, and packages to aid in rapid identification of cargoes, and an international cargo commodity numbering system.

The DOT requires that all freight containers, trucks, and rail cars transporting these materials display placards identifying the hazard class or classes of the materials they are carrying. The placards are diamond-shaped, 10 inches on a side, and color-coded, and they show an icon or graphic symbol depicting the hazard class (flammable, caustic, acid, radioactive, etc.). They are displayed on the ends and sides of transport vehicles. A four-digit identification number may also be displayed on some placards or on an adjacent rectangular orange panel. If you have spent any time on the roads, you have undoubtedly seen these placards or panels displayed on trucks and railroad tank cars. You may recognize some of the more common ones, such as “1993,” which covers a multitude of chemicals, including road tar, cosmetics, diesel fuel, and home heating oil. You may have also seen placards with the number “1203” (gasoline) on tankers filling the underground tanks at the local gas station.

In addition to truck and rail car placards, warning labels must be displayed on most packages containing hazardous materials. The labels are smaller versions (4 inches on a side) of the same placards used on vehicles. In some cases, more than one label must be displayed, in which case the labels must be placed next to each other. In addition to labels for each DOT hazard class, other labels with specific warning messages may be required. Individual containers also have to be accompanied by shipping papers that contain the proper product name, the four-digit ID number, and other important information about the hazards of the material.



Hazardous Chemicals in Buildings

The National Fire Protection Association (NFPA) has devised a marking system to alert firefighters to the characteristics of hazardous materials stored in stationary tanks and facilities. This system, known as NFPA 704M, can also assist citizens visiting a site in identifying the hazard presented by the stored substance. Use of the system is voluntary, unless specified by local codes.

The NFPA 704M label is diamond-shaped and is divided into four parts, or quadrants. The left quadrant, colored blue, contains a numerical rating of the substance's health hazard. Ratings are made on a scale of 0 to 4, with a rating of 4 indicating a danger level so severe that a very short exposure could cause serious injury or death. A 0, or no code at all in this quarter, means that no unusual hazard would result from the exposure.

The top quadrant of the NFPA symbol contains the substance's fire hazard rating. As you might expect, this quadrant is red. Again, number codes in this quadrant range from 0 to 4, with 4 representing the most serious hazard.

The NFPA label's right quadrant, colored yellow, indicates the substance's likelihood to explode or react. As with the health and fire hazard quadrants, ratings from 0 to 4 are used to indicate the degree of danger. If a 4 appears in this section, the chemical is extremely unstable, and even under normal conditions may explode or react violently. A 0 in this quadrant indicates the material is considered stable even in the event of a fire.

The bottom quadrant is white and contains information about any special hazards that may apply. There are three possible codes for the bottom quarter of the NFPA symbol:

1. OXY means this material is an oxidizer. It can easily release oxygen to create or worsen a fire or explosion hazard.
2. The symbol W indicates a material that reacts with water to release a gas that is either flammable or hazardous to health.
3. If the material is radioactive, the usual tri-blade "propeller" symbol for radioactivity will appear.

Guidelines for Handling HazMat Incidents

1. Once you are in a safe position uphill and upwind, try to identify the material. However, it cannot be emphasized enough that you *must* stay well away from the site. Do *not* be tempted to get just a little closer so that you can read placards or other items. If you cannot read these items using a spotting scope or binoculars, simply report what you can see from a safe position. If you are able to see from a safe position, look for:
 - The four-digit number on a placard or orange panel.
 - The four-digit number preceded by "UN/NA" on a shipping paper, package, or drum.
 - The name of the material on the shipping papers, placard, or package.
2. Call for help immediately and let the experts handle the situation. Remember, even ordinary firefighters and police are prohibited by federal law from taking certain actions at some

HazMat incidents. Do not attempt to personally take any action beyond your report and preventing others from approaching. This is an instance when it is vitally important to know your limitations, not just for your own safety, but also for the safety of others.

3. When reporting a HazMat incident, include the following information:

- Identify yourself.
- Give your current location and the location of the incident, i.e., street address or cross streets, road and mile marker, distance from nearest town, etc.
- Briefly describe what you see (from a distance), i.e., liquid spill, gaseous cloud, etc., and any placard numbers or other information you can safely see.
- If a gaseous cloud or liquid spill exists, give the direction the contaminant is flowing or moving. Give any pertinent weather or other information you can observe from a safe distance that might help the experts in responding to the incident. Be concise.

Reference Links

Details of the placards and emergency response procedures can be found in the comprehensive *DOT Emergency Response Guidebook*, copies of which may be available for your review at your local emergency management, police, sheriff, or fire department. A copy is also available online at:

<https://www.phmsa.dot.gov/sites/phmsa.dot.gov/files/docs/ERG2016.pdf>

NOTE: The 2016 version is the most recent Emergency Response Guide

The 2016 ERG manual is available at no-cost for both Apple and Android devices:

<https://www.phmsa.dot.gov/hazmat/erg/erg2016-mobileapp>

You may also consult your Local Emergency Planning Committee (LEPC) or State Emergency Response Commission (SERC) concerning what role Amateur Radio might have in your local plan.

For more information about hazardous materials in general, contact:

FEMA, Technological Hazards Division
Federal Center Plaza, 400 C St., SW
Washington, DC 20472
(202) 646-2861

Review

If you happen upon a hazardous materials incident, first take precautions to protect yourself and others with you by remaining at a safe distance, upwind and uphill. Next, report any basic

information you can safely gather, including placard legends and numbers, wind conditions, scene conditions, and other information to the appropriate public safety partner. Take no direct action except to report what you witness and to protect yourself and others.

Activities

1. Describe how you would handle the following situation:

You are assisting with damage assessment following a severe weather outbreak, reporting damage and casualties to the local fire and police agencies. Cresting a hill, you see a tank trailer overturned on the road ahead. No one else is around. A variable wind is blowing the leaking fumes in several directions unpredictably. You cannot see the placards on the truck from where you are.

Welcome to Topic 25 Knowledge Review

Please review the following questions to improve your understanding of this topic:

Question 1:

Which of the following *best* describes where you should be located when in the vicinity of a HazMat incident?

- a) Far enough away to ensure your safety.
- b) Downhill and downwind.
- c) Close enough to read the numbers on any placards with your naked eyes.
- d) Alongside emergency responders wearing exposure suits.

Question 2:

Which federal partner is responsible for warning the public about hazardous materials containers and shippers?

- a) Federal Emergency Management Agency.
- b) Federal Response Plan.
- c) National Communications System.
- d) Department of Transportation.

Question 3:

Before transmitting in the area of a HazMat incident, what should you always do?

- a) First identify the agents by reading the placard or container labels.
- b) Be far enough away so that no vapors or fumes are present.
- c) Wait to report the incident until police or fire officials have arrived.
- d) Take action to stop or contain any agents that might be leaking.

Question 4:

On the sides of transporting vehicles, how are different classes of hazardous materials identified?

- a) Placards.
- b) Four-digit numbers.
- c) Warning labels and/or icons.
- d) All of the above answers are correct.

Question 5:

Gasoline tankers filling the neighborhood gas station's underground tanks are identified with a placard bearing which of the following numbers?

- a) 1203
- b) 1993
- c) 2003
- d) 2706